Technical Indicators

Dabco TMEDA catalyst CAS 110-18-9 Evonik Germany

Dabco TMEDA is a tertiary amine-based foaming catalyst that facilitates urea

(water-isocyanate) reactions in a variety of hard and soft polyurethane foam

applications. It is the industry standard foaming catalyst for soft foams and is used in

TDI-based soft foam systems such as mattresses, seats and automobiles. It is also used

in combination with trimer catalysts in PIR laminated paperboard formulations. Dabco

TMEDA is also available in MDI, TDI/MDI, MDI High Resilience (HR) soft molding foams

as well as self-crusting and microcellular systems. It has a shelf life of 36 months.

CAS No.

Dabco TMEDA's CAS number is 110-18-9. This is a unique identifier for Dabco TMEDA

that is used to track and identify it throughout the supply chain. CAS numbers are also

used to search databases and other resources for information about Dabco TMEDA.

Physical and chemical properties

The physical and chemical properties of Dabco TMEDA are shown in the following

table:

Property

Value

Looks

Clear colorless liquid





Scent	A slight ammonia smell

Specific gravity 1.040

Boiling point 200 °C

Flash point 100 °C

Water soluble Miscible

Solubility in organic solvents miscibility

Features

Promotes urea (water-isocyanate) reaction

Used in a variety of hard and soft polyurethane foam applications

Industry standard foaming catalyst for soft foams

For TDI-based soft foam systems, such as mattresses, seats, and automobiles


Use in combination with trimer catalysts in PIR laminated cardboard formulations

Technical Indicators



Also available in MDI, TDI/MDI, MDI High Resilience (HR) soft molded foams as well as self-crusting and microcellular systems

The shelf life is 36 months



Application

- Soft polyurethane foam
- On-site casting polyurethane system
- PIR laminated cardboard
- TDI, TDI/MDI, MDI High Resilience (HR) Soft molded foam
- Self-crusting foam
- Microcellular foam

Pros

Technical Indicators

Promotes urea (water-isocyanate) reaction

Used in a variety of hard and soft polyurethane foam applications

Industry standard foaming catalyst for soft foams

Can be used in combination with trimer catalysts

Shelf life is 36 months

Cons

Corrosive to certain metals

Can have a strong odor

Combustible

Similarities and differences with similar products

Dabco TMEDA is similar to other tertiary amine-based foaming catalysts in that it

promotes the urea (water-isocyanate) reaction. However, it has a number of

advantages over other products, including its use in a variety of applications, industry

standard status for soft foams, and ability to be combined with trimer catalysts.

Precautions for Use

Wear gloves and safety goggles when handling the Dabco TMEDA.

Technical Indicators

Avoid contact with skin and eyes.

Keep away from heat sources and open flames.

Store in a cool, dry place.

Dispose of it properly according to local regulations.

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper

ventilation. After the original packaging, please fasten the packaging cover as soon as

possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous

membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and

change after work. Store contaminated clothes separately and use them after washing.

Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com